

# CS7,5 E



## FEATURES

- Heavy duty frame.
- Electrical motor.
- Compact design with easily removable motor.
- Adjustable handle height for all cutting depths.

## BENEFITS

- Robust, low vibration level.
- No gas emission, low noise level, adapted to confined areas.
- Easy transport.
- Ergonomic working position.

## PRODUCT DATA

Item No.	701846 23924
EAN 13 Code	5450248 333623

Supply Voltage / Power	400V 3~ / 7,5kW (10Hp)
Fuse/Generator	16A / 19 kVA
Blade x bore	Ø 800 x25,4mm
Max. cutting depth	320mm
Dimensions (LxWxH)	1270 x 580 x 1000mm
Weight	118kg

Tool speed RPM	1460 min <sup>-1</sup>
Starter	Electric
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	4,86 m/s <sup>2</sup>
Sound power / pressure level	94 dB (A) / 80 dB (A)



10HP



7,5kW



400V 3~

## PRODUCT COMPARISON



MAX CUT DEPTH



ADJUSTABLE HANDLE



DEPTH CONTROL HAND WHEEL



WATER HOSE CONNECTOR

## DIAMOND BLADE RECOMMENDATIONS FOR CS7,5 E



Substrate / Material	BETON
Recommended Product	EXTREME BETON
Diameter	800mm
Bore	25,4mm
Item No.	701846 01693
Page reference	18

SPARE PARTS FOR SOME MACHINES AVAILABLE ON **PAGE 120** OR VISIT OUR WEBSITE [www.nortonabrasives.com](http://www.nortonabrasives.com)

