

ISM/ISC SUPER

FEATURES

- Water distributors connectable to optional water supply system.
- Extended operating handle.
- Crank controlled cutting depth adjustment.
- Cutting head height setting by foot pedal and handle (ISM).

BENEFITS

- Wet cutting and dust free working conditions.
- Optimum cutting pressure application.
- Easy and accurate setting.
- Maximum user comfort.



ISM 3,75,3

Item No. 701846 13985
EAN 13 Code 5450248 231239



Supply Voltage/ Power	400V 3~ / 5,5kW (7,5Hp)
Fuse/Generator	32 A / 14 kVA
Blade x bore	Ø 500 x 25,4mm
Tool speed RPM	2062 min ⁻¹
Max. cutting depth	190mm
Max. cutting length	500mm
Flat table size (optional)	465 x 615mm
Tilting table (optional)	455 x 580mm
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	99 dB (A) / 85 dB (A)
Dimensions (LxWxH)	1400 x 760 x 1750mm
Weight	248kg

ISC 3,75,3

Item No. 701846 13986
EAN 13 Code 5450248 144861



Supply Voltage/ Power	400V 3~ / 5,5kW (7,5Hp)
Fuse/Generator	32 A / 14 kVA
Blade x bore	Ø 500 x 25,4mm
Tool speed RPM	2062 min ⁻¹
Max. cutting depth	190mm
Max. cutting length	750mm
Flat table size (optional)	710 x 615mm
Tilting table (optional)	710 x 610mm
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	99 dB (A) / 85 dB (A)
Dimensions (LxWxH)	1650 x 760 x 1750mm
Weight	280kg

PRODUCT FEATURES



MAX CUT DEPTH



Clipper's Tip

IMPORTANT

Conveyor carts, dust collectors and water supply systems are available as accessories. See selection chart below.



EXTREME UNI SILENCIO - 710846 30309



REFRACTORY - SEE RECOMMENDATION TABLE

HOW TO SELECT ISC AND ISM MASONRY SAWS AND ACCESSORIES

MAX. CUTTING LENGTH	FLAT OR MITRE CUT?	DRY OR WET CUTTING?	
		WET	DRY
<p>ISM UP TO 500mm</p>	<p>Tilting table 0 to 45° ISM: 3100 04702 ISC: 3100 04539</p> <p>Flat conveyor cart ISM: 3100 04704 ISC: 3100 04703</p>	<p>Water distribution kit 3100 04732</p>	<p>Hood 3100 04552</p> <p>Dust extractor bag type 3100 04544</p> <p>OR</p> <p>Dust extractor cabinet type 3100 04536</p>