

CSB1 D13

FEATURES

- Built in water tank.
- Manual hydraulic raise and lower of the blade.
- Built in lifting eye at centre of gravity.
- High resistance wheels with sealed heavy duty bearings.

BENEFITS

- Wet cutting autonomy in isolated locations.
- Quick, easy and accurate depth setting.
- Easy loading and transportation.
- Smooth and straight cutting.



PRODUCT DATA

Item No.	701846 13925	Power source	Diesel	Water tank capacity	25 L
EAN 13 Code	5450248 142829	Motor type	HATZ 1D81 Z	Tool speed RPM	1950 min ⁻¹
		Power	9,6kW (13 Hp)	Starter	Crank
		Blade x bore	Ø 500 x 25,4mm	Raise and lower	Manual hydraulic
		Max. cutting depth	190mm	Propelling	Automatic
		Dimensions (LxWxH)	1200 x 600 x 1040mm	Hand Arm Vibrations	5,08 m/s ²
		Weight	255kg	Sound power / pressure level	114 dB(A) / 101 dB(A)



13HP




9,6kW



DIESEL

PRODUCT FEATURES



MAX CUT DEPTH



BUILT-IN WATER TANK



MANUAL OR HYDRAULIC RAISE
& LOWER THE BLADE



BUILT-IN LIFTING EYE

DIAMOND BLADE RECOMMENDATIONS FOR CSB1 (DIESEL)

Substrate / Material	BETON	SILENCIO	ASPHALT	ALL MATERIALS
Recommended Product	EXTREME BETON	EXTREME BETON SILENCIO	EXTREME ASPHALT	PRO 4X4 EXPLORER
Diameter	500mm	500mm	500mm	500mm
Bore	25,4mm	25,4mm	25,4mm	25,4mm
Item No.	701846 01690	701846 30416	701846 94913	701846 02097
Page reference	24	25	54	44