

CGW

FEATURES

- Variable cutting guide
- Cutting head locking device
- Blade guard with removable cover
- Electrical water pump protected from slurries

BENEFITS

- Allows cutting at any angle without any additional tool
- Easy straight-through cutting
- Operator protection and easy access for blade change
- Reduced maintenance



PRODUCT DATA

Item No.	701846 29851
EAN 13 Code	5450248 407393

Supply Voltage/ Power KW	230V 1~
Fuse/Generator	16A / 6 kVA
Blade x bore (mm)	Ø 350 x 25,4
Tool speed RPM	2800 min ⁻¹
Dimensions (LxWxH) (mm)	980 x 600 x 1250
Dimensions (folded legs) (mm)	980 x 600 x 550
Weight	66kg

Tilting head	No
Max. cutting depth (mm)	110
Max. cutting length (mm)	500
Max. material height (mm)	150
Table size (mm)	440 x 340
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	92 dB (A) / 80 dB (A)



PRODUCT FEATURES



MAX CUT DEPTH



COMPENSATION SPRING



VARIABLE CUTTING GUIDE



SPLASH GUARD

DIAMOND BLADE RECOMMENDATIONS FOR CGW & CM351



Substrate / Material	BETON	SILENCIO	UNIVERSAL
Recommended Product	PRO BETON	EXTREME UNIVERSAL SILENCIO	EXTREME UNIVERSAL
Diameter x bore (mm)	350 x 25,4	350 x 25,4	350 x 25,4
Item No.	701846 27061	701846 28998	701846 12283
Page reference	20	27	26