

CT601



FEATURES

- Dead man handle
- Aluminium safety guard rings
- Mechanical blades pitch control
- Foldable arm and lifting eye

BENEFITS

- User's safety
- Light weight and user safety
- Setting accuracy for perfect surface finish
- Easy loading and transportation

CT601 MP

Item No.	701846 29945
EAN 13 Code	5450248 439998



4HP



2,9kW



PETROL

Included tools	Finishing blades and pan
Power Source	Petrol
Power kW (Hp)	2,9kW (4Hp)
Motor Type	HONDA GX 120
Supply Voltage	-
Fuse / Generator	-
Blade rotation diameter (clockwise) (mm)	600
Guard ring diameter (mm)	620
Distance to wall (mm)	10
Pitch control	Mechanical
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	93dB(A) / 81dB(A)
Dimensions (LxWxH) (mm)	1560 x 650 x 1060
Weight (without pans)	62kg

See CT601 accessories on CT600 UNO page

CT601 ME

Item No.	701846 29946
EAN 13 Code	5450248 440017



3HP



2,2kW



230V

Included tools	Finishing blades and pan
Power Source	Electric
Power kW (Hp)	2,2kW (3Hp)
Motor Type	-
Supply Voltage	230V 1~
Fuse / Generator	16A / 6kVA
Blade rotation diameter (clockwise) (mm)	600
Guard ring diameter (mm)	620
Distance to wall (mm)	10
Pitch control	Mechanical
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	91dB(A) / 79dB(A)
Dimensions (LxWxH) (mm)	1560 x 650 x 1060
Weight (without pans)	65kg

PRODUCT FEATURES



LIFTING HOOK



BLADE SAFETY GUARD



FOLDABLE MACHINE ARM



DISTANCE TO WALL: 10MM