

CST 120 UNO

FEATURES

- Robust conception
- Strong chrome-plated guiding bars
- Tilting and plunging head
- Removable feet

BENEFITS

- Reliable machine
- High precision cutting
- Adaptation of cutting depth and allows cuts up to 45°
- Easy transportation and storage



PRODUCT DATA

Item No.	701846 01846
EAN 13 Code	5450248 713999

Supply Voltage / Power W	230V 1~/ 2,0kW (3Hp)
Fuse/Generator	16A / 6kVA
Blade x bore (mm)	Ø 350 x 25,4m
Dimensions (LxWxH) (mm)	1650x580x1400
Dimensions (without legs) (mm)	1650x580x850
Weight	105kg

Max. cutting depth (mm)	110
Max. cutting length (mm)	1200
Max. material height (mm)	130
Table size (mm)	1200 x 560
Tool speed RPM	2800 min ⁻¹
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	88,5dB (A) / 73,5db (A)



PRODUCT FEATURES



MAX CUT LENGTH & DEPTH



CUTTING GUIDE

DIAMOND BLADE RECOMMENDATIONS FOR CST RANGE



Substrate / Material	BETON	SILENCIO	UNIVERSAL	NATURAL STONE	CERAM
Recommended Product	PRO BETON	EXTREME UNI SILENCIO	EXTREME UNIVERSAL	EXTREME GRANITE	EXTREME CERAM
Diameter x bore (mm)	350 x 25,4	350 x 25,4	350 x 25,4	350 x 25,4	350 x 25,4
Item No.	701846 27061	701846 28998	701846 12283	701846 01174	701846 30335
Page reference	20	27	26	42	38