

CB511

FEATURES

- Safety switch at end of cut
- Dry cut with minimal dust
- Easy to use
- Galvanised and folding table
- Lift ring, double lifting rail and wheels

BENEFITS

- Safety of use and time saving
- No water supply and water pump maintenance
- Low maintenance
- Space saving during transportation and storage
- Easy to move by crane, forklift or by hand
- More power, less dust, longer life



PRODUCT DATA

Item No.	701846 94702	Supply Voltage/ Power kW	230V 3~ / 1,85kW (2,5Hp)	Max. cutting length (mm)	660
EAN 13 Code	5450248 692393	Fuse/Generator	16A / 3 kVA	Max. material height (mm)	508
		Band size (mm)	3850 x 27	Table size (mm)	710 x 1060
		Dimensions (LxWxH) (mm)	1050x900x1840	Hand Arm Vibrations	<2,5m/s ²
		Weight	203kg	Sound power / pressure level	93,3 dB (A) / 80 dB (A)



2,5HP




1,85kW



230V

PRODUCT FEATURES



MAX CUT DEPTH



FOLDING TABLE



SAFETY OF USE



PRECISION CUT

BAND RECOMMENDATIONS FOR CB511

Substrate / Material	UNIVERSAL	UNIVERSAL
Recommended Product	EXTREME BAND CB511	PRO BAND CB511
Length (mm)	3850	3850
Item No.	710846 95024	710846 01811

IDEAL FOR...

Aerated fired clay blocks and autoclaved aerated concrete blocks

