

TR252



FEATURES

- Powerful 1500W motor
- Heavy duty guiding rail with tilting head
- Plunging head
- Built-in side extension
- Foldable handles, legs and transport wheels
- Cutting guide with angular setting
- Easy removal of the cutting table
- Rubber coated table + clamps

BENEFITS


- More comfortable to use and better results on hard materials
- Smooth cutting head movements, easy maintenance
- Adaptation of cutting depth allows step cutting of thick tiles
- Allows the cut of large/wide materials
- Easy transportation and space saving
- Precise angle cuts
- Easy clean of the water tray
- Perfectly straight cut even on the longest tiles

BLADE INCLUDED

- Ø 250mm Extreme Ceram Turbo

PRODUCT DATA

Item No.	701846 94289	Supply Voltage / Power W	230V 1~ / 1500W	Max. cutting depth at 90° / at 45° (mm)	15 / 10
EAN 13 Code	5450248 596592	Fuse/Generator	16A / 3 kVA	Max. cutting length (mm)	1200
		Blade x bore (mm)	Ø 250 x 25,4	Table size (mm)	1200 x 565
		Dimensions (LxWxH) (mm)	1860 x 600 x 1170	Tool speed RPM	2950 min ⁻¹
		Tilting head	0 - 45°	Hand Arm Vibrations	< 2,5 m/s ²
		Weight	75kg	Sound power / pressure level	87 dB (A) / 73 dB (A)



1200mm
MAX CUT LENGTH



PRODUCT FEATURES



PLUNGING CUTTING HEAD



CUTTING GUIDE INCLUDED

DIAMOND BLADE RECOMMENDATIONS FOR TR250 H



Substrate / Material	CERAM
Recommended Product	EXTREME CERAM TURBO
Blade x bore (mm)	250 x 25,4
Item No.	701846 25428
Page reference	38