

CSB1 P21



FEATURES

- Heavy duty jig welded steel frame
- Removable water tank
- Automatic forward propulsion
- Manual and hydraulic raise and lower of the blade

BENEFITS


- Robust and reliable
- Adapt machine to your specific needs
- Better comfort of use
- Quick, easy and accurate depth setting

PRODUCT DATA

Item No.	701846 45495	Power source	Petrol	Water tank capacity	Optional (25l accessory)
EAN 13 Code	5450248 530794	Motor type	HONDA GX630	Tool speed RPM	1775 min ⁻¹
		Power kW (Hp)	15kW (20 Hp)	Starter	Electric
		Blade x bore (mm)	Ø600 x 25,4	Raise and lower	Manual hydraulic
		Max. cutting depth (mm)	225	Propelling	Automatic
		Dimensions (LxWxH) (mm)	1200 x 600 x 1100	Hand Arm Vibrations	3,35 m/s ²
		Weight	240kg	Sound power / pressure level	107 dB(A)/89 dB(A)



PRODUCT FEATURES



MAX CUT DEPTH

CONTROL BOX

MANUAL OR HYDRAULIC RAISE & LOWER THE BLADE

REMOVABLE WATER TANK (OPTIONAL)

DIAMOND BLADE RECOMMENDATIONS FOR CSB1 (PETROL)

Substrate / Material	BETON	BETON	ASPHALT	ASPHALT
Recommended Product	EXTREME BETON	PRO BETON	EXTREME ASPHALT 10	PRO ASPHALT
Diameter (mm)	600	600	600	600
Bore (mm)	25,4	25,4	25,4	25,4
Item No.	701846 01691	701846 11982	701846 40192	701846 11980
Page reference	18	20	46	47