

JCW JUNIOR

FEATURES

- Cutting length of 600mm
- Blade guard always horizontal
- Mechanical water pump
- Transport wheels and removable legs

BENEFITS

- Precision for cutting large materials
- Protection and safety
- Lifespan and efficiency
- Easy transport and storage



JCW 600 1,30,1 Electric

Item No. 701846 30306
EAN 13 Code 5450248 414131



Supply Voltage/ Power kW	230V 1~ / 2,2kW (3 Hp)
Fuse/Generator	16A / 6 kVA
Blade x bore (mm)	Ø400 x 25,4
Tool speed RPM	2700 min ⁻¹
Max. cutting depth (mm)	150
Max. cutting length (mm)	600
Max. material height (mm)	250
Table size (mm)	400 x 490
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	89 dB (A) / 78 dB (A)
Dimensions (LxWxH) (mm)	1280 x 590 x 1460
Dimensions (folded legs) (mm)	1280 x 590 x 880
Weight	104kg

JCW 600 1,65.P Petrol

Item No. 701846 93499*
EAN 13 Code 5450248 575498



Power kW	4,8kW (6,5Hp)
Engine Type	Petrol / Honda GX200
Blade x bore (mm)	Ø400 x 25,4
Tool speed RPM	2700 min ⁻¹
Max. cutting depth (mm)	150
Max. cutting length (mm)	600
Max. material height (mm)	250
Table size (mm)	400 x 490
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	105 dB (A) / 93 dB (A)
Dimensions (LxWxH) (mm)	1280 x 590 x 1460
Dimensions (folded legs) (mm)	1280 x 590 x 880
Weight	109kg

* Available on request.

PRODUCT FEATURES



MAX CUT DEPTH



BLADE GUARD ALWAYS HORIZONTAL



CUTTING GUIDE



TRANSPORTATION WHEELS

DIAMOND BLADE RECOMMENDATIONS FOR JCW & CM401



Substrate / Material	BETON	SILENCIO	UNIVERSAL
Recommended Product	PRO BETON	EXTREME UNIVERSAL SILENCIO	EXTREME UNIVERSAL
Diameter x bore (mm)	400 x 25,4	400 x 25,4	400 x 25,4
Item No.	701846 27062	701846 40270	701846 11438
Page reference	20	27	26