

CT600 UNO

FEATURES

- 34kg light weight
- Dead man handle
- Mechanical blade pitch control

BENEFITS

- Easy to transport
- User's safety
- Setting accuracy for perfect surface finish



PRODUCT DATA

Item No.	701846 94230	Included tools	Finishing blades & pan	Guard ring diameter (mm)	610
EAN 13 Code	5450248 594680	Power Source	Electric	Distance to wall (mm)	25
		Power kW (Hp)	1,1 kW (1,5Hp)	Pitch control	Mechanical
		Motor Type	Electric	Hand Arm Vibrations	< 2,5 m/s ²
		Supply Voltage	230	Sound power / pressure level	91dB(A) / 71dB(A)
		Fuse / Generator	16A/6kVA	Dimensions (LxWxH) (mm)	1330 x 610 x 950
		Blade rotation ø (clockwise) (mm)	600mm	Weight (without pans)	34kg



PRODUCT FEATURES



COMPENSATION SPRING



FOLDABLE MACHINE ARM



BLADES SAFETY GUARD RINGS



DELIVERED WITH FINISHING BLADES & PAN

ACCESSORIES CT600 UNO & CT601

1



2



3



	DIMENSIONS L x L (mm)	FIXING THREAD	SPACING	ITEM No.	EAN 13 CODE
1 - Floating pan	Ø600	Mechanical stop	-	3100 04554	5450248 089179
2 - Finishing blades (set of 4)	230 x 120	M6	100	3103 69479	5450248 440185
3 - Feet skates (set of 2)	-	-	-	3100 04551	5450248 089063