

MITRE SAW / TABLE SAW



MITRE SAW

- Heavy-duty motors deliver impressive power and demonstrates excellent durability
- Front bevel control offering a range of 45° right to 45° left for precision cutting
- Adjustable mitre detent plate with nine positive detent stops ensure optimal cutting accuracy
- True-Line Laser keeps the operator in line at all times
- Pivoting LED work light keeps the cut illuminated, so the light always shines on the workpiece
- In-line horizontal "D" grip handle with two-position safety trigger is ideal for right or left handed users
- Quick-action mitre detent lock with single-motion thumb lever that releases or bypasses detent index points
- Includes vertical vice, dust bag and blade wrench

STAND

- Durable steel structure that supports up to 130 kg
- Compact folding design for easy storage and portability
- Telescoping extends up to 2520mm for added support
- Additional stand supports provide convenient vertical storage
- Mitre saw quick-release mounting brackets allows easy and secure mounting of the mitre saw to stand
- Heavy duty 200mm wheels provide high level mobility to, from, and around the jobsite

PRODUCT FEATURES

DESCRIPTION	CWM 216	CWM 254	STAND
Item No.	70184608463	70184608464	310538156
Supply voltage	230V 1 ~ 50 Hz	230V 1 ~ 50 Hz	-
Power	1400 W	1800W	-
Rotation Speed (RPM)	5000	4500	-
Max blade x bore	216x30mm	254x30mm	-
Dimensions (L x W x H)	800x600x450mm	970x600x450 mm	1170 to 2520x530x820mm
Hand Arm Vibration	<2.5m/s ²	<2.5m/s ²	-
Sound Power/ Pressure Level	89 dB (A) 100 dB (A)	92 dB (A) 104 dB (A)	-
Weight	16.8 kg	20.5 kg	19,5kg
Mitre Range	48° right to 48° left	52° left to 60° right	-
Bevel Range	45°right to 45° left	45°right to 45° left	-

BLADE WITH MACHINE

FOR CWM 216
70184608498
216x2.8/1.8x30
Z40 WF.216.30.Z40.1

FOR CWM 254
70184608499
254x3.2/2.2x30
Z48 WF.254.30.Z48.1



MAX DEPTH X MAX LENGTH OF CUT		MITRE CUT ANGLE		
		45° LEFT	0°	45° RIGHT
BEVEL CUT ANGLE	45° RIGHT	CWM 216: 18 x 215mm CWM 254: 25 x 215mm	CWM 216: 18 x 305mm CWM 254: 25 x 305mm	CWM 216: 18 x 215mm CWM 254: 25 x 215mm
	0°	CWM 216: 62 x 215mm CWM 254: 90 x 215mm	CWM 216: 62 x 305mm CWM 254: 90 x 305mm	CWM 216: 62 x 215mm CWM 254: 90 x 215mm
	45° LEFT	CWM 216: 30 x 215mm CWM 254: 40 x 215mm	CWM 216: 30 x 305mm CWM 254: 40 x 305mm	CWM 216: 30 x 215mm CWM 254: 40 x 215mm