

CM351 UNO



FEATURES

- Adjustable depth stop on tilting head
- Extra large 600x600mm conveyor cart with anti-slipping rubber surface and tilted wheels
- Removable robust plastic water tray

BENEFITS

- Allows 45° bevel cut, with embedded slot in the conveyor cart
- Step cutting and full-depth cutting are possible in both 90° and 45° head position
- Improved cart stability. Wide materials are more stable and are easier to cut.
- Easier cleaning and handling

PRODUCT DATA

Item No.	701846 30312	Supply Voltage/ Power kW	230V 1~ / 2,2kW	Tilting head	0 or 45°
EAN 13 Code	5450248 509394	Fuse/Generator	16A / 6 kVA	Max. cutting depth (mm)	110
		Blade x bore (mm)	Ø 350 x 25,4	Max. cutting length (mm)	700
		Tool speed RPM	2800 min ⁻¹	Max. material height (mm)	150
		Dimensions (LxWxH) (mm)	1146 x 815 x 1270	Table size (mm)	600 x 600
		Dimensions (folded legs) (mm)	1146 x 725 x 639	Hand Arm Vibrations	2,2 m/s ²
		Weight	69kg	Sound power / pressure level	87 dB (A) / 73 dB (A)



3HP



2,2kW



230V

PRODUCT FEATURES



MAX CUT DEPTH



TILTING HEAD & WIDE CONVEYOR



REMOVABLE WATER TRAY



EASY TRANSPORT



NATURAL STONE

EXTREME GRANITE

350 x 25,4

701846 01174

42

ALL MATERIALS

PRO 4X4 EXPLORER

350 x 25,4

701846 02093

36

SPARE PARTS FOR SOME MACHINES
AVAILABLE ON **PAGE 103** OR VIA
OUR WEBSITE www.nortonabrasives.com

