

TR232 L

FEATURES

- Heavy duty guiding rail
- Tilting head
- Built-in side extension
- Foldable handles, legs and transport wheels
- Cutting guide with angular setting
- Easy removal of the cutting table
- Rubber coated table + clamps

BENEFITS

- Smooth cutting head movements, easy maintenance
- Perfect for mitre cut from 0° to 45°
- Allows the cut of large/wide materials
- Easy transportation and space saving
- Precise angle cuts
- Easy clean up of the water tray
- Perfectly straight cut even on the longest tiles

BLADE INCLUDED

- Ø 230mm Extreme Ceram Turbo



PRODUCT DATA

Item No.	701846 01103
EAN 13 Code	5450248 699491

Supply Voltage / Power W	230V 1~ /1,1kW
Fuse/Generator	16A / 3 kVA
Blade x bore (mm)	Ø 230 x 25,4
Dimensions (LxWxH) (mm)	1860 x 600 x 1175
Tilting head	0 - 45°
Weight	72kg

Max. cutting depth at 90° / at 45° (mm)	15 / 10
Max. cutting length (mm)	1200
Table size (mm)	1200 x 565
Tool speed RPM	2950 min ⁻¹
Hand Arm Vibrations	< 2,5 m/s ²
Sound power / pressure level	71 dB (A) / 79 dB (A)



1100w



230v

1200mm
MAX CUT LENGTH



PRODUCT FEATURES



ADJUSTABLE CLAMPS FOR FIXING THE TILES



ANGULAR CUTTING GUIDE / RUBBER-COVERED TABLE

DIAMOND BLADE WITH MACHINE FOR TR232 L



Substrate / Material	CERAM
Recommended Product	EXTREME CERAM TURBO
Blade x bore (mm)	230 x 25,4
Item No.	701846 27653
Page reference	38