

CG252

The CG252 is a light-weight and compact 250mm single-head grinding machine for grinding and levelling of small to medium size floor preparation, and removal of coating or adhesives.

The grinding head can be oriented at 90° and the front of the safety guard can be opened to grind edges of walls. With a weight of only 60kg, it is easier to operate during grinding operations, and less tiring for the operator. The foldable arm make it easy to transport.

CG252 can be combined with a dust extractor (CV324 or CV360) or used for wet grinding thanks to a water connection.



PRODUCT DATA

Item No.	701846 94290	Power kW / Supply Voltage	2,2kW (3Hp) / 230V 1~	Vacuum connector	45mm
EAN 13 Code	5450248 596608	Fuse / Generator	16A / 6 kVA	Hand Arm Vibrations	< 2,5 m/s ²
		Working width	250mm	Dimensions (LxWxH)	1180 x 520 x 1150mm
		Tool speed RPM	1410 min ⁻¹	Weight	60kg



3HP



2,2kW



230V

FEATURES

- 250mm working width
- Orientable grinding head
- Level setting on the back
- Light and compact
- Low vibrations

PRODUCT FEATURES



THE GRINDING HEAD CAN BE ORIENTED AT 90° & THE FRONT OF THE GUARD REMOVED.






FOLDABLE ARM FOR TRANSPORT

BENEFITS

- Designed for small to medium size floors
- Able to grind the edges of walls
- Quick and easy setting of the machine
- Easy to transport and carry upstairs
- Easy and comfortable usage

GRINDING HEAD RECOMMENDATIONS



Grinding Head Colour	RED	GREEN	BLUE
Substrate / Material	BETON	BETON	BETON
Diameter (mm)	250mm	250mm	250mm
Floor Type	HARD	MEDIUM	SOFT
Item No.	701846 27118	701846 27117	701846 27116
Page reference	155	155	155